



Caracteristicas:

2U-TSB6909-989 6L

- | 1*card TSB6909Vx2
- | Aluminum alloy structure, Customizable panels
- | Support Intel Ivy Bridge Processor
- | Support 1*DDR3L Memory, up to 8GB
- | 1*mSATA slot (Support 2.5 inch HDD)

Product Specifications

Processor	Intel Core i3-3110M 2 Core 2 Thread Frequency: 2.4GHz
Chipset	i3-3110M (Opt.1005M/i3-2350M/i5-2520M/3320M/i7-3520M/3610M/3630QM)
BIOS	AMI EFI BIOS
Memory	1*DDR3L 1600MHz SO-DIMM Memory slot Up to 8GB
Storage	1*mSATA SSD; 1*SATA (Support 2.5 inch HDD/SSD)
Display chip	Integrated Intel HD 600 Graphics Card
Display port	1*VGA port; 1*HDMI port (Optional)
Front I/O interface	6*1225 2.5G Ethernet port 2*Intel 82599 SFP+ 2*USB3.0 1*Console
Back I/O interface	1*VGA, 1*AC Power input 1*Power Button
Expansion slot	2*Mini PCIe Channel for WiFi/Bluetooth/4G
Ethernet port	6*1G Ethernet port
Other functions	Power-on boot; Scheduled boot; Wake-up on LAN; PXE boot; Watchdog
Power supply	Mean Well LRS-50-12 Input: 100-240V~1.0A Output: 12V 4.2A
Certificate	CE、CCC、FCC、ROHS
Size	440x257x45(mm) (Without rack ear)
Working Temperature	-0~+50°C (Commercial HDD); -20°C~+50°C (Industrial SSD); Surface Air flow
Environment Humidity	5~90RH, Non-condensing
Weight	
Packing Size	560*540*260MM